



Notes

- **HOUSING:** Formed aluminum housing with cast aluminum backplate. High transmission clear refractive acrylic lens.
- **FINISH:** Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- **DRIVER:** Integral LED driver compatible with 0-10v, Triac, or ELV dimming.
- **MOUNTING:** Aluminum post supplied with base plate mounting. Standard height is 36".

1 Fixture Number
B-919 6"W x 6"H 36" Oah.

2 Finish
Housing
 Standard Painted Finishes (PT)

3 Lamping
 Includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

B-919

LED Options	Lumens	Wattage
E13 Downlight	1550 (initial)	13

4 LED Color Temp
 27: 2700K
 30: 3000K
 35: 3500K
 40: 4000K

5 LED Dimming
 D0: 0-10v
 D1: Triac (Leading Edge)*
 D2: ELV (Trailing Edge)

6 Voltage Options
 120: 120 volt
 277: 277 volt (Not available with incandescent lamp options)

7 Diffuser Options
 CRA: Clear refractive acrylic lens

1

Fixture #

2

Housing
(Finish)

3

Lamping

4

Color Temp

5

Dimming

6

Voltage

7

Diffuser