



Notes

- **FINISH:** Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- **HOUSING:** Consists of extruded aluminum frame with solid aluminum or brass bars and machined aluminum or brass bar details over an extruded white acrylic cylinder diffuser.
- **MOUNTING:** Fixture supplied with gasketed universal mounting plate for installation over standard octagonal junction box.
- ETL listed to UL standards for wet locations.
- Fluorescent ballasts rated to - 22-degree F

1 Fixture Number

DE-610	7.25"W x 16"H x 4" Ext.
DE-612	9.25"W x 20"H x 5" Ext.
DE-614	9.25"W x 28"H x 5" Ext.

2 Finish

End Caps/Frame	Bars
Standard Painted Finishes (PT)	Standard Painted Finishes (PT)

3 Lamping

Includes integral wet location rated 120-277v 1-100% dimming driver compatible with 0-10v controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

DE-610

LED Options	Lumens	Wattage
E11	818 (initial)	11

Non-LED Lamps

2NT40: (2) 40 watt T-10 incandescent

DE-612

LED Options	Lumens	Wattage
E17	1226 (initial)	17

Non-LED Lamps

2N60: (2) 60 watt incandescent

DE-614

LED Options	Lumens	Wattage
E23	1636 (initial)	23

Non-LED Lamps

3N60: (3) 60 watt incandescent

4 LED Color Temp

27: 2700K
30: 3000K
35: 3500K
40: 4000K

5 LED Dimming

D0: 0-10v

6 Voltage Options

120: 120 volt
277: 277 volt (Not available with incandescent lamp options)

7 Diffuser Options

WH: Opal White Acrylic
FX: Faux Alabaster Acrylic

8 Fixture Options

PC: Photo Cell

1	2	2	3	4	5	6	7	8
Fixture #	End Caps/Frame (Finish)	Bars (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser	Fixture Option