



## Notes

- **FINISH:** Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- **HOUSING:** Consists of an adjustable fabricated aluminum reflector housing and fabricated aluminum wall mounting plate.
- **MOUNTING:** Fixture mounts to a standard octagonal junction box.
- \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

### 1 Fixture Number

<b>HO-740</b>	17.5"W x 7.5"H x 10.75" Ext.
<b>HO-742</b>	26"W x 7.5"H x 10.75" Ext.
<b>HO-744</b>	30"W x 7.5"H x 10.75" Ext.

### 2 Finish

Standard Painted Finishes (PT)

### 3 Lamping

LED option includes integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

#### HO-740

LED Options	Lumens	Wattage
S16	995 (delivered)	16

#### HO-742

LED Options	Lumens	Wattage
S32	3440 (initial)	32

#### HO-744

LED Options	Lumens	Wattage
S64	6880 (initial)	64

### 4 LED Color Temp

27: 2700K  
30: 3000K  
35: 3500K  
40: 4000K

### 5 LED Dimming

D0: 0-10v  
D1: Triac (Leading Edge)\*  
D2: ELV (Trailing Edge)

### 6 Voltage Options

120: 120 volt  
277: 277 volt (Not available with incandescent lamp options)

1

Fixture #

2

Finish  
(Finish)

3

Lamping

4

Color Temp

5

Dimming

6

Voltage