



## Notes

- **FINISH:** Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- **OAH** is standard unless specified.
- 
- **HOUSING:** Extruded aluminum corner supports, machined accents, steel stem, and fabricated steel square canopy can be ordered with complementary finishes. Internal frame components in highly reflective white enameled aluminum.
- **MOUNTING:** Fixture is supplied with a universal mounting strap assembly that attaches to a standard octagonal junction box.
- **CIRCUITS:** Dual-level circuiting for interior lamps/downlight standard.
- ETL listed to UL standards for dry and damp locations
- \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

### 1 Fixture Number

- LP-360** 10"W x 10"H x 10"L 35" Oah.  
**LP-362** 10"W x 24"H x 10"L 49" Oah.

### 2 Finish

- Brushed Solid Aluminum (BA)  
 Standard Painted Finishes (PT)

### 3 Lamping

LED options includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

#### LP-360

LED Options	Lumens	Wattage
P16	2200 (initial)	16

#### Non-LED Lamps

1N75: (1) 75 watt incandescent

#### LP-362

LED Options	Lumens	Wattage
P27 Body only w/bottom lens (27W)	2730 (delivered)	27
P63 Body (27w) + Downlight (36w)	5471 (delivered)	63

#### Non-LED Lamps

1N150: (1) 150 watt incandescent

### 4 LED Color Temp

- 27: 2700K  
 30: 3000K  
 35: 3500K  
 40: 4000K

### 5 LED Dimming

- D0: 0-10v  
 D1: Triac (Leading Edge)\*  
 D2: ELV (Trailing Edge)

### 6 Voltage Options

- 120: 120 volt  
 277: 277 volt (Not available with incandescent lamp options)

### 7 Diffuser Options

- WH: Opal White Acrylic  
 CD: Ambia configured diffuser (specify option)

1	2	3	4	5	6	7
Fixture #	Finish (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser