

Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- HOUSING: Fabricated and roll-formed heavy gauge solid aluminum.
- MOUNTING: Fixture mounts to a standard octagonal junction box.
- ETL listed to UL standards for dry and damp locations
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

1 Fixture Number
DS-710 12"W x 7"H x 4" Ext.

2 Finish
Housing & Trim
Brushed Solid Aluminum (BA)
Standard Painted Finishes (PT)

3 Lamping
LED options includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

DS-710

LED Options	Lumens	Wattage
S8	1193 (initial)	8

Non-LED Lamps


1N60: (1) 60 watt incandescent

4 LED Color Temp
27: 2700K
30: 3000K
35: 3500K
40: 4000K

5 LED Dimming
D0: 0-10v
D1: Triac (Leading Edge)*
D2: ELV (Trailing Edge)

6 Voltage Options
120: 120 volt
277: 277 volt (Not available with incandescent lamp options)

7 Panel Options



8 Fixture Options
BL: Bottom Lens (included with LED options)

1	2	3	4	5	6	7	8
Fixture #	Housing & Trim (Finish)	Lamping	Color Temp	Dimming	Voltage	Panel	Fixture Option