



Notes

- **FINISH:** Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- **LED option** includes bottom white acrylic diffuser.
- **HOUSING:** Consists of a solid spun aluminum cylinder housing with a white acrylic cylinder diffuser.
- **MOUNTING:** Fixture mounts to a standard octagonal junction box.
- ETL listed to UL standards for dry and damp locations
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

1 Fixture Number
LB-158 6"W x 12.5"H x 9" Ext.

2 Finish
Housing & Trim
Brushed Solid Aluminum (BA)
Standard Painted Finishes (PT)

3 Lamping
LED option includes integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

LB-158

LED Options	Lumens	Wattage
C38	3118 (delivered)	38

Non-LED Lamps

2N60: (2) 60 watt incandescent

4 LED Color Temp
27: 2700K
30: 3000K
35: 3500K
40: 4000K

5 LED Dimming
D0: 0-10v
D1: Triac (Leading Edge)*
D2: ELV (Trailing Edge)

6 Voltage Options
120: 120 volt
277: 277 volt (Not available with incandescent lamp options)

7 Diffuser Options
WH: Opal White Acrylic

1	2	3	4	5	6	7
Fixture #	Housing & Trim (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser