



## Notes

- **FINISH:** Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- **HOUSING:** Solid aluminum top and bottom end caps, extruded aluminum corner posts and laser-cut aluminum accent panel. Solid aluminum or wood bar stock accents.
- **MOUNTING:** Fixture mounts to a standard octagonal junction box.
- ETL listed to UL standards for dry and damp locations
- \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

### 1 Fixture Number

**LB-094** 8"W x 16"H x 4" Ext.

### 2 Finish

**End plates, trim bars, trim panels**  
Brushed Solid Aluminum (BA)  
Standard Painted Finishes (PT)

### Bar Trim

Brushed Solid Aluminum (BA)  
Standard Painted Finishes (PT)  
Wood Trim (WT)

### 3 Lamping

LED option includes integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

### LB-094

LED Options	Lumens	Wattage
S7	612 (delivered)	7

### Non-LED Lamps

2NT60: (2) 60 watt T-10 incandescent

### 4 LED Color Temp

27: 2700K  
30: 3000K  
35: 3500K  
40: 4000K

### 5 LED Dimming

D0: 0-10v  
D1: Triac (Leading Edge)\*  
D2: ELV (Trailing Edge)

### 6 Voltage Options

120: 120 volt  
277: 277 volt (Not available with incandescent lamp options)

### 7 Diffuser Options

CB: Cobalt Blue Acrylic  
PF: Perforated Aluminum  
WH: Opal White Acrylic

1	2	2	3	4	5	6	7
Fixture #	End plates, tr (Finish)	Bar Trim (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser