



## Notes

- CIRCUITS: Two-circuit wiring for uplight/downlight standard.
- CP-126 and CP-128 are shipped in segments and require some assembly.
- DIFFUSER: Bottom white 1/8" thick extruded acrylic lens. Top: Clear 1/8" thick extruded acrylic lens.
- ETL listed to UL standards for dry and damp locations.
- FINISH: Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- HOUSING: Rolled aluminum extrusion. LED Drivers integral for static color models, remote DMX driver for RGBW option.
- MOUNTING: Field-adjustable aircraft cable suspension to separate mouting locations and power cord to painted canopy. OAH is standard unless specified.

### 1 Fixture Number

<b>CP-122</b>	3"W x 3"H x 24" Dia. 24" Oah.
<b>CP-123</b>	3"W x 3"H x 36" Dia. 36" Oah.
<b>CP-124</b>	4"W x 3"H x 48" Dia. 48" Oah.
<b>CP-126</b>	4"W x 3"H x 72" Dia. 72" Oah.
<b>CP-128</b>	4"W x 3"H x 96" Dia. 96" Oah.

### 2 Finish

#### Housing

Standard Painted Finishes (PT)

### 3 Lamping

Includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

#### CP-122

LED Options	Lumens	Wattage
DCH57		
CH112 Downlight	5700 delivered	112
RGBW Coming soon!		

#### CP-123

LED Options	Lumens	Wattage
DCH85		
CH167 Downlight	8600 delivered	167
RGBW Coming soon!		

#### CP-124

LED Options	Lumens	Wattage
DCH112		
CH223 Downlight	11450 delivered	223
RGBW Coming soon!		

#### CP-126

LED Options	Lumens	Wattage
DCH167		
CH334 Uplight + Downlight	22350 delivered	334
RGBW Coming soon!		

#### CP-128

LED Options	Lumens	Wattage
DCH223		
CH445 Uplight + Downlight	29800 delivered	445
RGBW Coming soon!		

### 4 LED Color Temp

27: 2700K  
30: 3000K  
35: 3500K  
40: 4000K

### 5 LED Dimming

D0: 0-10v  
D1: Triac (Leading Edge)\*  
D2: ELV (Trailing Edge)

### 6 Voltage Options

120: 120 volt  
277: 277 volt (Not available with incandescent lamp options)

### 7 Diffuser Options

WH: Opal White Acrylic

### 8 Stem Options



Aircraft Cable  
(CBL)

1	2	3	4	5	6	7	8
Fixture #	Housing (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser	Stem