



## Notes

- OAH is standard unless specified.
- FINISH: Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- HOUSING: White 1/8" thick extruded acrylic cylinder diffuser with white painted aluminum bottom disk. Aluminum driver housing. Integral driver option increases H and OAH dimensions by 11.5".
- MOUNTING: Fixture supplied with canopy, 45-degree swivel ball and hanger for mounting to standard octagon junction box.
- DOWNLIGHT: Downlight increases H and OAH dimensions by 2".
- CIRCUITS: Dual-level circuiting for interior lamps and downlight (if specified) standard.
- \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.
- DKC CANOPY: Canopy is 5" dia. (D2 dim.) for P30, P44, P58 options. All others use 13" dia canopy (D3 dim.).
- ETL listed to UL standards for dry and damp locations.

### 1 Fixture Number

<b>LP-572-04</b>	24"H x 4" Dia. 48" Oah.
<b>LP-572-06</b>	24"H x 6" Dia. 48" Oah.
<b>LP-573-04</b>	36"H x 4" Dia. 60" Oah.
<b>LP-573-06</b>	36"H x 6" Dia. 60" Oah.
<b>LP-574-04</b>	48"H x 4" Dia. 72" Oah.

<b>LP-574-06</b>	48"H x 6" Dia. 72" Oah.
<b>LP-576-04</b>	72"H x 4" Dia. 96" Oah.
<b>LP-576-06</b>	72"H x 6" Dia. 96" Oah.
<b>LP-578-04</b>	96"H x 4" Dia. 120" Oah.
<b>LP-578-06</b>	96"H x 6" Dia. 120" Oah.

### 2 Finish

#### Housing, Stem & Canopy

Standard Painted Finishes (PT)

### 3 Lamping

Includes remote or integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency. Downlight separately circuited.

#### LP-572

LED downlight is COB array with 1,225 delivered lumens @ 3500K.

LED Options	Lumens	Wattage
P30 Body Only (24W)	3021 (delivered)	24
P41 Body (24w) + Downlight (11w)	4246 (delivered)	35

#### LP-573

LED downlight is COB array with 1,225 delivered lumens @ 3500K.

LED Options	Lumens	Wattage
P44 Body Only (36W)	4532 (delivered)	36
P56 Body (36w) + Downlight (11w)	5757 (delivered)	47

#### LP-574

LED downlight is COB array with 1,225 delivered lumens @ 3500K.

LED Options	Lumens	Wattage
P58 Body Only (48W)	6042 (delivered)	48
P69 Body (48w) + Downlight (11w)	7267 (delivered)	59

#### LP-576

LED downlight is COB array with 1,225 delivered lumens @ 3500K.

LED Options	Lumens	Wattage
P87 Body Only (72W)	9064 (delivered)	72
P98 Body (72w) + Downlight (11w)	10289 (delivered)	83

#### LP-578

LED downlight is COB array with 1,225 delivered lumens @ 3500K.

LED Options	Lumens	Wattage
P116 Body Only (96W)	12085 (delivered)	96
P127 Body (96w) + Downlight (11w)	13310 (delivered)	107

### 4 LED Color Temp

27: 2700K  
30: 3000K  
35: 3500K  
40: 4000K

### 5 LED Dimming

D0: 0-10v  
D1: Triac (Leading Edge)\*  
D2: ELV (Trailing Edge)

### 6 Downlight Optics Options

B50: 50-deg. beam reflector

### 7 Voltage Options

120: 120 volt  
277: 277 volt (Not available with incandescent lamp options)

### 8 Diffuser Options

WH: Opal White Acrylic

### 9 Stem Options



Single Stem  
(SIN)

Aircraft cable with cord  
(KBL)

### 10 Fixture Options

INT: Integral LED drivers. Increases H and OAH dimensions by 11.5"  
REM: Remote driver box  
DKC: Disk ceiling driver canopy

1

2

3

4

5

6

7

8

9

10

Fixture # Housing, Stem (Finish) Lamping Color Temp Dimming Downlight Opti Voltage Diffuser Stem Fixture Option