



## Notes

- ETL listed to UL standards for dry, damp, or wet locations.
- HOUSING: Formed aluminum housing with cast aluminum backplate. High transmission clear refractive acrylic lens.
- FINISH: Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- DRIVER: Integral LED driver compatible with 0-10v, Triac, or ELV dimming.
- MOUNTING: Fixture for installation over standard octagonal junction box.

**1 Fixture Number**  
B-721 10"W x 10"H x 12.5" Ext.

**2 Finish**  
**Housing**  
Standard Painted Finishes (PT)

**3 Lamping**  
Includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

### B-721

LED Options	Lumens	Wattage
E32 Downlight	4240 (initial)	32

**4 LED Color Temp**  
27: 2700K  
30: 3000K  
35: 3500K  
40: 4000K

**5 LED Dimming**  
D0: 0-10v  
D1: Triac (Leading Edge)\*  
D2: ELV (Trailing Edge)

**6 Voltage Options**  
120: 120 volt  
277: 277 volt (Not available with incandescent lamp options)

**7 Diffuser Options**  
CRA: Clear refractive acrylic lens

<b>1</b>	<b>2</b>	<b>3</b>	<b>4</b>	<b>5</b>	<b>6</b>	<b>7</b>
Fixture #	Housing (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser