



## Notes

- **HOUSING:** Formed aluminum housing with cast aluminum backplate. High transmission clear refractive acrylic lens.
- **FINISH:** Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- **DRIVER:** Integral LED driver compatible with 0-10v, Triac, or ELV dimming.
- **MOUNTING:** Aluminum post supplied with base plate mounting. Standard height is 36".

**1 Fixture Number**  
B-919 6"W x 6"H 36" Oah.

**2 Finish**  
**Housing**  
Standard Painted Finishes (PT)

**3 Lamping**  
Includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

### B-919

LED Options	Lumens	Wattage
E13 Downlight	1550 (initial)	13

**4 LED Color Temp**  
27: 2700K  
30: 3000K  
35: 3500K  
40: 4000K

**5 LED Dimming**  
D0: 0-10v  
D1: Triac (Leading Edge)\*  
D2: ELV (Trailing Edge)

**6 Voltage Options**  
120: 120 volt  
277: 277 volt (Not available with incandescent lamp options)

**7 Diffuser Options**  
CRA: Clear refractive acrylic lens

1

Fixture #

2

Housing  
(Finish)

3

Lamping

4

Color Temp

5

Dimming

6

Voltage

7

Diffuser