



Notes

- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems. 33
- FINISH: Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- HOUSING: Consists of white thermoformed acrylic with laser-cut accent panels and painted canopy.
- MOUNTING: Fixture mounts to a standard octagonal junction box.
- ETL listed to UL standards for dry and damp locations

1 Fixture Number
CC-097 16.25"W x 6.5"H x 16.25"L

2 Finish
Trim
Brushed Solid Aluminum (BA)
Standard Painted Finishes (PT)

Cross Symbol
Brushed Solid Aluminum (BA)
Standard Painted Finishes (PT)

3 Lamping
All LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

LED Options	Lumens	Wattage
C26	2178 (delivered)	26
C38	3118 (delivered)	38

Non-LED Lamps
3N60: (3) 60 watt incandescent

4 LED Color Temp
27: 2700K
30: 3000K
35: 3500K
40: 4000K

5 LED Dimming
D0: 0-10v
D1: Triac (Leading Edge)*
D2: ELV (Trailing Edge)

6 Voltage Options
120: 120 volt
277: 277 volt (Not available with incandescent lamp options)

7 Diffuser Options
WH: Opal White Acrylic

8 Panel Options

