



Notes

- OAH is standard unless specified.
- FINISH: Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- HOUSING: Consists of acrylic or spun aluminum bowls with aluminum arms.
- MOUNTING: CP-260 & CP-262: Fixture specified with brushed or painted finish supplied with swivel hanger for mounting to standard octagon junction box. Fixture specified with brass material supplied with swivel hanger requiring attachment to structure using a ceiling fan rated electrical box. CP-261 & CP-263: Structural support is required for this heavy fixture. 2 x 4 blocking or 1/2" IP stud extending 1/2" below finished ceiling through center of octagonal junction box is required.
- ETL listed to UL standards for dry and damp locations
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

1 Fixture Number

| | |
|---------------|--------------------------|
| CP-260 | 9"H x 60" Dia. 30" Oah. |
| CP-261 | 9"H x 60" Dia. 30" Oah. |
| CP-262 | 10"H x 80" Dia. 42" Oah. |
| CP-263 | 10"H x 80" Dia. 42" Oah. |

2 Finish

- Standard Painted Finishes (PT)
- Brushed Solid Aluminum (BA)

3 Lamping

All LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

CP-260

| LED Options | Lumens | Wattage |
|---------------------------------|--------------------------------------|---------|
| CH64 Two Bowls - Up & Downlight | 1097 up/1097 dn per bowl (delivered) | 64 |

Non-LED Lamps

6N100: (6) 100 watt incandescent

CP-261

| LED Options | Lumens | Wattage |
|-----------------------------------|--------------------------------------|---------|
| CH128 Four Bowls - Up & Downlight | 1097 up/1097 dn per bowl (delivered) | 128 |

Non-LED Lamps

12N100: (12) 100 watt incandescent

CP-262

| LED Options | Lumens | Wattage |
|-----------------------------------|--------------------------------------|---------|
| CH129R Two Bowls - Up & Downlight | 2545 up/1855 dn per bowl (delivered) | 129 |

Non-LED Lamps

8N100: (8) 100 watt incandescent

CP-263

| LED Options | Lumens | Wattage |
|------------------------------------|--------------------------------------|---------|
| CH256R Four Bowls - Up & Downlight | 2545 up/1855 dn per bowl (delivered) | 256 |

Non-LED Lamps

16N100: (16) 100 watt incandescent

4 LED Color Temp

- 27: 2700K
- 30: 3000K
- 35: 3500K
- 40: 4000K

5 LED Dimming

- D0: 0-10v
- D1: Triac (Leading Edge)*
- D2: ELV (Trailing Edge)

6 Voltage Options

- 120: 120 volt
- 277: 277 volt (Not available with incandescent lamp options)

7 Diffuser Options

- PT: Standard Painted Finishes
- BA: Brushed Solid Aluminum
- WH: Opal White Acrylic
- FX: Faux Alabaster Acrylic

8 Stem Options



| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 |
|-----------|-----------------|---------|------------|---------|---------|----------|------|
| Fixture # | Finish (Finish) | Lamping | Color Temp | Dimming | Voltage | Diffuser | Stem |