



Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- HOUSING: Consists of a thermoformed acrylic diffuser with machined aluminum or brass trim.
- MOUNTING: Fixture mounts to a standard octagonal junction box.
- ETL listed to UL standards for dry and damp locations
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

- 1 Fixture Number**
DS-664 15"W x 7.5"H x 4" Ext.
- 2 Finish**
Brushed Solid Aluminum (BA)
Standard Painted Finishes (PT)
Polished Brass (PB)
Solid Antique Brass (SAB)
Faux Antique Brass (FAB)

- 3 Lamping**
LED options includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

DS-664

LED Options	Lumens	Wattage
S7	612 (delivered)	7

Non-LED Lamps
1NT60: (1) 60 watt T-10 incandescent

- 4 LED Color Temp**
27: 2700K
30: 3000K
35: 3500K
40: 4000K
- 5 LED Dimming**
D0: 0-10v
D1: Triac (Leading Edge)*
D2: ELV (Trailing Edge)

- 6 Voltage Options**
120: 120 volt
277: 277 volt (Not available with incandescent lamp options)

- 7 Diffuser Options**
WH: Opal White Acrylic
FX: Faux Alabaster Acrylic

