



Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- HOUSING: Solid aluminum top and bottom end caps, extruded aluminum corner posts and laser-cut aluminum accent panel. Extruded aluminum arms and wall plate.
- MOUNTING: Fixture mounts to a standard octagonal junction box.
- ETL listed to UL standards for wet locations.
- Fluorescent ballasts rated to - 22-degree F

1 Fixture Number

DE-250 8.7"W x 16.3"H x 9.2" Ext.
DE-252 11.5"W x 24.5"H x 13.5" Ext.

2 Finish

Trim Standard Painted Finishes (PT)
Panel Standard Painted Finishes (PT)
 Raw Copper (CU)

3 Lamping

Includes integral wet location rated 120-277v 1-100% dimming driver compatible with 0-10v controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

DE-250

LED Options	Lumens	Wattage
E11	818 (initial)	11
E11/1QP75		

Non-LED Lamps

1N100 / 1QP75: (1) 100 watt incandescent & (1) 75 watt PAR30 halogen med. base

DE-252

LED Options	Lumens	Wattage
E17	1226 (initial)	17
E17/1QP75		

Non-LED Lamps

4N60 / 1QP75: (4) 60 watt incandescent & (1) 75 watt PAR30 halogen med. base

4 LED Color Temp

27: 2700K
 30: 3000K
 35: 3500K
 40: 4000K

5 LED Dimming

D0: 0-10v

6 Voltage Options

120: 120 volt
 277: 277 volt (Not available with incandescent lamp options)

7 Diffuser Options

WH: Opal White Acrylic
 FX: Faux Alabaster Acrylic

8 Panel Options



G1



G2



G3



G4



G5



G6

1	2	2	3	4	5	6	7	8
Fixture #	Trim (Finish)	Panel (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser	Panel